





## LAVAPEN P OPEN

This system performs the successful washing of small and medium sized mechanical parts.

In this configuration (P), the machine is fed by compressed air only for the use of detergents at room temperature.

The machine is available in 2 version:

- P (cold pneumatic)
- C (maximum temperature adjustable up to 60°C)



Dimensions and layout	LP3_P_OP	LP4_P_OP
depth (P)	82 cm	92 cm
height (H)	140 cm	140 cm
loading height (AC)	100 cm	100 cm
noise LT (RU)	75 dBa	75 dBa
washing area (AL)	95 x 70 cm	120 x 80 cm
weight (W)	75 Kg	90 Kg
width (L)	111 cm	136 cm

Connections	LP3_P_OP	LP4_P_OP
Compressed air intake	F 1/4"	F 1/4"
Steam extraction	Ø50 mm	Ø50 mm
Tank liquid drain	F 1"	F 1"

Technical data	LP3_P_OP	LP4_P_OP
Load capacity	70 kg	70 kg
Pump 1	2 bar 5 lt/min	2 bar 5 lt/min
Tank 1 capacity	75 lt	90 lt

Technical features	LP3_P_OP	LP4_P_OP
Adjustable feet +/- 50mm	★	★
Compressed air blowing gun	★	★
Drain valves for emptying tanks	★	★
Intake and delivery pump hose (easy maintenance)	★	★
Internal ed external welding bleaching	★	★
Manually adjustable washing pressure	★	★
Pedal-controlled washing action	★	★
Special ergonomic washing brush	★	★

Technical features	LP3_P_OP	LP4_P_OP
Structure and sheet metal in contact with liquid in AISI 304L stainless steel	★	★

Accessories	LP3_P_OP	LP4_P_OP	Cod.
Compact pneumatic oil separator	✓	✓	MD
Increased loading capacity to 150 kg	✓	✓	ACC150
Machine equipped with wheels for handling [D]	✓	✓	RUO
Rotating workpiece support table with manual idle rotation	✓	✓	PROT
Stainless steel cartridge filter (10/25/50 micron)	✓	✓	FCX

**Accessories notes legend**

[D]: the two accessories are incompatible, they cannot be installed on the same system

★ = included in the basic model, ✓ = available on request, X = not available